



NovoDock H 1300 and H 1500

Flexible loading solution for your logistics

Product characteristics

- retrospectively installed to existing loading area
- minimal disruption during installation
- Green Solution Product
- robust steel construction
- i-Vision control



NovoDock H 1300 und H 1500

Docking pods offer many advantages as compared to conventional internally constructed loading bays.

- variable concept for the use of telescopic lip and swing lip levellers
- space-saving construction in straight or saw tooth angled construction.
- additional storage space in building
- flexible forms of docking pod
- reduction of energy consumption for heated warehouses

Structure

The docking pod consists of the following units:


- a steel base frame with integrated dock leveller (NovoDock P 1300i or P 1500i)
- a structure in various models

A stable hot-dipped steel frame square tube construction forms the structure of the docking pod. Depending on the requirements or specific appearance, it can be supplied as follows:

• Type Standard:

Cladding with trapezoidal metal sheet up to the top edge of the steel base frame, precoated in RAL colours


Inside: RAL 9002 (grey white)
 Outside: RAL 9002 (grey white),
 RAL 9006 (white aluminium)



• Type ISO:

Cladding with 40-mm ISO panel up to top edge of the steel base frame, precoated in RAL colours

Inside: RAL 9002 (grey white)
 Outside: RAL 9002 (grey white),
 RAL 9006 (white aluminium)



• Type Basic frame:

Possible only with steel frame construction for foundation by customer



Technical data

Nominal lengths 2000, 2500, 3000, 3500, 4000, 4500 mm
 Nominal widths 3300, 3500 mm
 Ramp heights 950 to 1500 mm

Work needed in preparation for the installation

This depends on the preferred installation method. Please request our technical data sheets.

Options / Accessories

- supplied with telescopic lip or swing lip leveller
- hot-dipped coating of steel pedestal
- variable work angle
- roof drainage
- front connection
- painted in RAL colours of customer's choice
- other dimensions and load bearing capacities upon request
- large selection of steel and rubber impact buffers
- loading light
- side walls up to lower edge of dock leveller
- dock shelter

Side walls up to top edge of dock leveller (standard)



Angled saw tooth construction type



Subject to misprints and technical alterations without notice.